







# 110 FASTON TERMINAL

## ▶ FEMALE TERMINAL (mm)

Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm <sup>2</sup>	AWG		W	L	E		
	<b>804001-41BS</b>	<b>0 2</b>	0.25	0.5~1.3	20~16	0.5	3.7	15.5	6.3	12,000	
	<b>804001-21BS</b>	<b>0 2</b>	0.25	0.3~0.5	22~20	0.5	3.7	15.5	6.3	15,000	
	<b>804002-21BS</b>	<b>0 2</b>	0.25	0.13~0.3	26~22	0.5	3.7	15.5	6.3	15,000	
	<b>804001-01BS</b>	<b>0 2</b>	0.25	0.13~0.3	26~22	0.5	3.7	15.5	6.3	15,000	
	<b>804005BS</b>	<b>0 2</b>	0.25	0.5~1.3	20~16	0.8	3.7	15.5	6.3	12,000	
	<b>804006BS</b>	<b>0 2</b>	0.25	0.3~0.5	22~20	0.8	3.7	15.5	6.3	15,000	
	<b>804007BS</b>	<b>0 2</b>	0.25	0.13~0.3	26~22	0.8	3.7	15.5	6.3	15,000	
	<b>804006-1BS</b>	<b>0 2</b>	0.25	0.3~0.5	22~20	0.6	3.7	15.5	6.3	15,000	
	<b>804011BS</b>	<b>0 2</b>	0.25	0.5~1.3	20~16	0.3	3.7	15.5	6.3	15,000	
	<b>804015BS</b>	<b>0 2</b>	0.25	0.13~0.3	26~22	0.15	3.7	15.5	6.3	15,000	
	<b>804016BS</b>	<b>0 2</b>	0.25	0.13~0.3	26~22	0.3	3.7	15.5	6.3	15,000	
	<b>804030BS</b>	<b>0 2</b>	0.25	0.3~0.8	22~18	0.5	3.7	11.5	6.0	20,000	
	<b>804031BS</b>	<b>0 2</b>	0.25	0.3~0.8	22~18	0.8	3.7	11.5	6.0	20,000	
	<b>804032BS</b>	<b>0 2</b>	0.25	0.3~0.8	22~18	0.3	3.7	11.5	6.0	20,000	
	<b>*804036BS</b>	<b>N</b>	0.25	-	-	0.8	3.7	17.5	6.0	10,000	
	<b>804001-1BS</b>	<b>0 2</b>	0.25	0.13~0.3	26~22	0.5	3.7	15.5	6.3	15,000	





# 110 FASTON TERMINAL

▶ MALE TERMINAL (mm)

Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm <sup>2</sup>	AWG		W	L	E		
	<b>805104BS</b>	<b>0 2</b>	0.5	0.8~1.3	18~16	0.5	2.8	20.5	11.7	10,000	
	<b>805106BS</b>	<b>0 2</b>	0.5	0.22~0.5	24~20	0.5	2.7	15.5	7.5	12,000	
	<b>805107BS</b>	<b>0 2</b>	0.5	0.5~0.8	20~18	0.5	2.7	15.5	7.5	12,000	
	<b>805108BS</b>	<b>0 2</b>	0.8	0.22~0.5	24~20	0.8	2.7	15.5	7.5	12,000	
	<b>805109BS</b>	<b>0 2</b>	0.8	0.5~0.8	20~18	0.8	2.7	15.5	7.5	10,000	
	<b>805113-01PS</b>	<b>0 5</b>	0.8	0.3~0.8	22~18	0.8	3.1	22.5	10.0	2,500	
	<b>816151-81KS</b>	<b>S</b>	0.4	2.0~3.0	14~12	0.8	2.8	26.7	10.2	3,000	


# 110 FASTON TERMINAL

▶ TERMINAL (mm)

Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm <sup>2</sup>	AWG		W	L	E		
	<b>805101BS</b>	<b>0 S</b>	0.5	0.8~1.3	18~16	0.5	2.8	20.5	11.6	10,000	
	<b>805102BS</b>	<b>0 S</b>	0.5	0.22~0.5	24~20	0.5	2.8	20.5	11.6	10,000	
	<b>805121BS</b>	<b>0 2</b>	0.5	0.8~1.3	18~16	0.5	2.8	20.8	12.1	5,000	
	<b>805123BS</b>	<b>0 2</b>	0.5	0.22~0.5	24~20	0.5	2.8	20.8	12.1	7,000	
	<b>804101BS</b>	<b>0 2</b>	0.25	0.5~1.3	20~16	0.5	3.7	15.5	6.5	10,000	
	<b>804102BS</b>	<b>0 2</b>	0.25	0.3~0.8	22~18	0.5	3.7	15.5	6.5	10,000	
	<b>804121BS</b>	<b>0 2</b>	0.25	0.3~0.8	22~18	0.5	3.7	15.5	6.3	5,000	
	<b>805150BL</b>	<b>2</b>	0.5	-	-	0.5	2.8	36.2	12.2	5,000	



# 110 FASTON TERMINAL

## ▶ TERMINAL (mm)

Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm <sup>2</sup>	AWG		W	L	E		
	<b>804111CBS</b>	<b>OS</b>	0.3	0.3~0.8	22~18	0.5	4.0	15.5	7.0	5,000	
	<b>804111C-41BS</b>	<b>OS</b>	0.3	0.3~0.8	22~18	0.5	4.0	15.5	7.0	5,000	
	<b>804111SBS</b>	<b>OS</b>	0.25	0.3~0.8	22~18	0.5	4.0	15.5	7.0	5,000	



SUITABLE TERMINAL:805101/805121

## ▶ TERMINAL (mm)


Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm <sup>2</sup>	AWG		W	L	E		
	<b>816321BS</b>	<b>S</b>	0.3	1.3~2.0	16~14	0.8	2.8	26.6	8.85	5,000	
	<b>816323BS</b>	<b>S</b>	0.3	0.3~0.5	22~20	0.8	2.8	26.6	8.85	6,000	
	<b>816211PS</b>	<b>S</b>	0.3	1.3~2.0	16~14	0.8	4.0	22	13.2	5,000	
	<b>816213PS</b>	<b>S</b>	0.3	0.3~0.5	22~20	0.8	4.0	22	13.2	5,000	

# 110 FASTON TERMINAL


## ▶ TERMINAL (mm)

Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm <sup>2</sup>	AWG		W	L	E		
	<b>805162BS</b>	<b>S</b>	0.35	0.8~1.3	18~16	0.8	2.8	21.7	12.4	8,000	
	<b>805163BS</b>	<b>S</b>	0.35	0.3~0.8	20~18	0.8	2.8	21.7	12.4	8,000	
	<b>804162BS</b>	<b>S</b>	0.25	0.8~1.3	18~16	0.8	3.7	15.5	6.5	5,000	
	<b>804163BS</b>	<b>S</b>	0.25	0.3~0.8	20~18	0.8	3.7	15.5	6.5	5,000	

## ▶ TERMINAL (mm)






Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm <sup>2</sup>	AWG		W	L	E		
	<b>816221KS</b>	<b>S</b>	0.4	3.3~5.5	12~10	0.8	4.0	22.0	8.5	4,000	

## ▶ MALE TERMINAL (mm)

Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm <sup>2</sup>	AWG		W	L	E		
	<b>816102BS</b>	<b>S</b>	0.4	0.8~2.0	18~14	0.8	2.8	22.6	6.9	5,000	
	<b>816103BS</b>	<b>S</b>	0.4	0.3~0.8	22~18	0.8	2.8	22.6	6.9	6,000	



# 110 FASTON TERMINAL

## MALE TERMINAL (mm)

Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm <sup>2</sup>	AWG		W	L	E		
	<b>816121BS</b>	<b>S</b>	0.25	0.3~0.8	22~18	0.5	2.7	29.5	3.5	5,000	
	<b>816130BS</b>	<b>O</b>	0.4	0.22~0.5	24~20	0.8	2.8	17.5	8.5	7,000	
	<b>816132BS</b>	<b>O</b>	0.4	0.22~0.5	24~20	0.8	2.8	17.5	8.5	7,000	
	<b>830101-21BS</b>	<b>S</b>	0.4	0.8~1.3	18~16	0.8	1.6	24.7	9.8	6,000	
	<b>830111-21BS</b>	<b>S</b>	0.4	0.8~1.3	18~16	0.8	2.8	24.4	9.8	3,500	

# 110 TERMINAL

▶ TERMINAL (mm)

Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm <sup>2</sup>	AWG		W	L	E		
	<b>635401-81PS</b>	<b>S</b>	0.3	2.0~3.5	14~12	0.6	3.9	20.0	5.4	3,000	
	<b>635402-51PS</b>	<b>S</b>	0.3	0.8~1.3	18~16	0.6	3.9	20.0	5.4	3,000	
	<b>635403-21PS</b>	<b>S</b>	0.3	0.3~0.8	22~18	0.6	3.9	20.0	5.4	5,000	