





# PTC TERMINAL

## ▶ TERMINAL (mm)

| Fig   | Part No.            | Finish               | Thick. | Wire Range      |       | Tab Thick. | Dimension (mm) |      |      | Q'ty  | STD. |
|---|---------------------|----------------------|--------|-----------------|-------|------------|----------------|------|------|-------|------|
|   |                     |                      |        | mm <sup>2</sup> | AWG   |            | W              | L    | E    |       |      |
|    | <b>691202-21KS</b>  | <b>S</b><br><b>5</b> | 0.3    | 0.3~0.5         | 22~20 | 0.6        | 2.1            | 19.4 | 10.1 | 5,000 |      |
|    | <b>691400-51PS</b>  | <b>S</b>             | 0.3    | 2.0             | 14    | 0.8        | 3.1            | 21   | 9.9  | 3,000 |      |
|   | <b>691401-41PS</b>  | <b>S</b>             | 0.3    | 1.0-2.5         | 17-13 | 0.8        | 3.1            | 21   | 9.9  | 3,000 |      |
|   | <b>691402-21PS</b>  | <b>S</b><br><b>5</b> | 0.3    | 0.5-1.0         | 20-18 | 0.8        | 3.1            | 21   | 9.9  | 3,000 |      |
|   | <b>691402-21KS</b>  | <b>S</b>             | 0.3    | 0.5-1.0         | 20-18 | 0.8        | 3.1            | 21   | 9.9  | 3,000 |      |
|   | <b>691403-01PS</b>  | <b>S</b>             | 0.3    | 0.2-0.5         | 24-20 | 0.8        | 3.1            | 21   | 9.9  | 3,000 |      |
|   | <b>691401S-41PS</b> | <b>S</b>             | 0.3    | 1.0-2.5         | 17-13 | 0.8        | 3.1            | 18.8 | 9.8  | 3,000 |      |
|   | <b>691402S-21PS</b> | <b>S</b><br><b>7</b> | 0.3    | 0.5-1.0         | 20-18 | 0.8        | 3.1            | 18.8 | 9.8  | 4,500 |      |
|  | <b>691411-41PS</b>  | <b>S</b>             | 0.3    | 1.0-2.5         | 17-13 | 0.8        | 3.1            | 19   | 9.8  | 4,000 |      |
|   | <b>691411-21PS</b>  | <b>S</b>             | 0.3    | 0.5~0.8         | 20~18 | 0.8        | 3.1            | 19   | 9.8  | 4,000 |      |
|   | <b>691412-21PS</b>  | <b>S</b><br><b>5</b> | 0.3    | 0.5~0.8         | 20~18 | 0.8        | 3.1            | 19   | 9.8  | 4,000 |      |
|  | <b>816321BS</b>     | <b>S</b>             | 0.3    | 1.3~2.0         | 16~14 | 0.8        | 2.8            | 26.6 | 8.85 | 5,000 |      |
|   | <b>816323BS</b>     | <b>S</b>             | 0.3    | 0.3~0.5         | 22~20 | 0.8        | 2.8            | 26.6 | 8.85 | 6,000 |      |