




POSITIVE LOCK TERMINAL

▶ 110 TERMINAL (mm)

Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm ²	AWG		W	L	E		
	801101-21BS	OS	0.25	0.3~0.5	22~20	0.5	3.7	17.3	6.0	5,000	
	801101-41BS	OS	0.25	0.5~1.3	20~16	0.4	3.7	17.3	6.0	5,000	

▶ 187 TERMINAL (mm)



Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm ²	AWG		W	L	E		
	801201-21BS	OS	0.3	0.22~0.5	24~20	0.5	5.6	17.3	6.3	3,500	
	801201-51BS	OS	0.3	0.8~2.0	18~16	0.5	5.6	17.3	6.3	3,500	
	801205BS	OS	0.3	0.8~2.0	18~16	0.8	5.6	17.3	6.3	3,500	
	801206BS	OS	0.3	0.22~0.5	24~20	0.8	5.6	17.3	6.3	3,500	
	801220BS	O2	0.3	0.3~0.8	22~18	0.5	5.8	13.5	7.2	10,000	
	801226BS	OS	0.3	0.3~0.8	22~18	0.8	5.8	13.5	7.2	10,000	

▶ 187 FLAG TERMINAL (mm)



Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm ²	AWG		W	L	E		
	811201-51BS	OS	0.3	0.8~2.0	18~16	0.5	5.7	13.5	6.3	3,500	
	811202-51BS	OS	0.3	0.8~2.0	18~16	0.8	5.7	13.5	6.3	3,500	
	811205-51BS	OS	0.35	0.8~2.0	18~16	0.5	5.7	13.5	6.3	3,500	
	811206-51BS	OS	0.35	0.8~2.0	18~16	0.8	5.7	13.5	6.3	3,500	

POSITIVE LOCK TERMINAL

▶ 250 TERMINAL (mm)



Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm ²	AWG		W	L	E		
	801402BS	0 S	0.4	0.8~2.0	18~14	0.8	7.5	23.0	9.3	2,000	
	801411BS	0 S	0.4	3.5~5.5	12~10	0.8	7.6	23.1	6.6	3,000	
	801412BS	0 S	0.4	0.8~2.0	18~14	0.8	7.6	22.8	6.5	4,000	
	801413BS	0 S	0.4	0.3~0.8	22~18	0.8	7.6	22.8	6.5	4,000	
	801415BS	0 2	0.4	3.5~5.5	12~10	0.8	7.5	19.5	6.3	3,000	
	801416BS	0 2	0.4	0.8~2.0	18~14	0.8	7.5	19.5	6.3	5,000	
	801417BS	0 2	0.4	0.3~0.8	22~18	0.8	7.5	19.5	6.3	5,000	

▶ 250 FLAG TERMINAL (mm)

Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm ²	AWG		W	L	E		
	810420-51BS	S	0.4	1.3~2.0	16~14	0.8	7.4	18.0	7.6	2,000	
	810420-21BS	S	0.4	0.5~1.3	20~16	0.8	7.4	18.0	7.6	2,000	
	811401BS	S	0.4	2.0~3.5	14~12	0.8	7.7	15.5	9.0	2,000	
	811402BS	S	0.4	1.3~2.0	16~14	0.8	7.7	15.5	9.0	2,000	

POSITIVE LOCK TERMINAL



▷ 205 TERMINAL (mm)

Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm ²	AWG		W	L	E		
	801331BS	OS	0.4	2.0	14	0.8	6.3	21.0	6.5	5,000	
	801332BS	OS	0.4	0.3~0.8	22~18	0.8	6.3	21.0	6.5	5,000	
	810321-51BS	S	0.4	0.8~2.0	18~14	0.8	6.1	21.0	6.3	3,000	
	810321-21BS	S	0.4	0.3~0.5	22~20	0.8	6.1	21.0	6.3	3,500	
	810321-01BS	S	0.4	0.5~0.8	20~18	0.8	6.1	21.0	6.3	3,500	


P-LOCK

POSITIVE LOCK TERMINAL

▶ 205 TERMINAL (mm)

Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm ²	AWG		W	L	E		
	801302-51PS	S	0.4	1.3~3.5	16~12	0.8	6.3	21.0	6.1	4,500	
	801303-21PS	S	0.4	0.3~1.3	22~16	0.8	6.3	21.0	6.1	5,000	
	805332-41BS	S	0.4	1.3~3.5	16~12	0.8	5.0	26.7	15.0	4,000	
	805332-21BS	S	0.4	0.3~1.3	22~16	0.8	5.0	26.7	15.0	5,000	

▶ 250 TERMINAL (mm)

Fig	Part No.	Finish	Thick.	Wire Range		Tab Thick.	Dimension (mm)			Q'ty	STD.
				mm ²	AWG		W	L	E		
	653201BS	S	0.4	3.5~5.5	12~10	0.8	7.6	20.8	8.0	3,000	
	653202BS	S	0.4	0.8~1.3	18~16	0.8	7.6	20.8	8.0	3500	
	653203BS	S	0.4	0.3~0.5	22~20	0.8	7.6	20.8	8.0	3,500	